

FABRISORB™

Decorative Fabric Wrapped Custom ACOUSTICAL Panels








Sound Absorption Coefficients

6-7 PCF Glass Fiber	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	NRC
1"	.14	.27	.80	1.11	1.14	1.14	.85
2"	.22	.81	1.24	1.30	1.21	1.16	1.15



FEATURES & BENEFITS

- High-performance
- Architecturally decorative designs
- Custom engineered & manufactured
- Reduced noise & reverberation / echo
- Custom colors and sizes available
- Easy to install

MATERIAL

6-7 lb. density glass fiber with woven fabric and micro-perforated vinyl facings.

APPLICATIONS

Auditoriums, bars, restaurants, conference and board rooms, open office areas, sports and entertainment venues, retail stores, theaters, schools, audiophile rooms, lobbies, recording studios, gymnasiums, houses of worship, music practice and band rooms, airports, condos, apartments, and more.

SIZES

Standard: 2' x 2', 2' x 4', 4' x 8'. Custom up to 4' x 10'.

THICKNESS

1", 1-1/8", 2", 2-1/8". Custom thicknesses available.

COLORS

A wide range of fabric colors. Other specialty facings available.

FLAMMABILITY

Class A Fire Rated per ASTM E84.

INSTALLATION

Adhesive, Impaling Clips, Z-Clips, Hook & Loop Fasteners, Magnetic Clips, Rotofast.

ACOUSTICAL DATA

NRC 1" .85 NRC 2" 1.15

Test Reports & Additional Information Can be Found at:

 $www.acoustical surfaces.com/fabric_panel/fabric-wrapped-wall-panels.html\\$

Edge Details



Square







Custom Graphics Available























ACOUSTICAL SURFACES, INC.

Celebrating Over 40 Years – SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION SPECIALISTS! 952.448.5300 | 800.448.0121 | sales@acousticalsurfaces.com | www.acousticalsurfaces.com

